

(12) **United States Patent**
Strbac

(10) **Patent No.:** **US 12,636,403 B2**
(45) **Date of Patent:** ***May 26, 2026**

(54) **FIREARM TRIGGER MECHANISM**

(56) **References Cited**

(71) Applicant: **ABC IP, LLC**, Dover, DE (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Mladen Thomas Strbac**, Cleveland, OH (US)

659,507 A 10/1900 Browning
2,056,975 A 10/1936 Michal, Jr.
(Continued)

(73) Assignee: **ABC IP, LLC**, Dover, DE (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

DE 582963 C 8/1933
DE 4008351 A1 9/1991
(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

(21) Appl. No.: **19/033,141**

Statutory Invention Registration No. H107, Inventor: Bauer, Published Aug. 5, 1986 (8 pages).

(22) Filed: **Jan. 21, 2025**

(Continued)

(65) **Prior Publication Data**

Primary Examiner — J. Woodrow Eldred

US 2025/0170297 A1 May 29, 2025

(57) **ABSTRACT**

Related U.S. Application Data

(63) Continuation of application No. 18/665,926, filed on May 16, 2024, now Pat. No. 12,274,807, which is a (Continued)

(51) **Int. Cl.**

F41A 19/24 (2006.01)
A61L 24/00 (2006.01)
A61L 24/04 (2006.01)

(52) **U.S. Cl.**

CPC **A61L 24/0036** (2013.01); **A61L 24/0015** (2013.01); **A61L 24/043** (2013.01);
(Continued)


(58) **Field of Classification Search**

CPC F41A 19/24; F41A 19/10; F41A 19/15;
F41A 19/16; F41A 17/46

See application file for complete search history.

A trigger mechanism that can be used in AR-pattern firearms has a hammer, a trigger member, a disconnecter, a locking member, and a “three position” safety selector having safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer such that the disconnecter hook catches the hammer hook, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer causing the trigger member to be forced to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter when the bolt carrier reaches the substantially in-battery

(Continued)



position the user can pull the trigger member to fire the firearm without manually releasing the trigger member. The locking member is pivotable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position and a second position at which the locking member does not mechanically block the trigger member allowing the trigger member to be moved to the released position. The locking member is spring biased toward the first position and moved against the spring bias to the second position by contact from the bolt carrier during forward movement of the bolt carrier as the bolt carrier reaches a substantially in-battery position.

55 Claims, 18 Drawing Sheets

Related U.S. Application Data

continuation of application No. 18/346,423, filed on Jul. 3, 2023, now Pat. No. 12,036,336, which is a continuation of application No. 18/048,572, filed on Oct. 21, 2022, now Pat. No. 11,724,003.

(60) Provisional application No. 63/297,884, filed on Jan. 10, 2022.

(52) U.S. Cl.

CPC *F41A 19/24* (2013.01); *A61L 2300/252* (2013.01); *A61L 2300/418* (2013.01); *A61L 2400/04* (2013.01); *A61L 2430/36* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

2,139,691 A 12/1938 Michal, Jr.
2,367,280 A 1/1945 Hyde
2,765,562 A 10/1956 Roper et al.
3,045,555 A 7/1962 Stoner
3,292,492 A 12/1966 Sturtevant
3,301,133 A 1/1967 Sturtevant
3,670,442 A 6/1972 Kennedy et al.
4,023,465 A 5/1977 Inskip
4,057,003 A 11/1977 Atchisson
4,151,670 A 5/1979 Rath
4,276,808 A 7/1981 York
4,433,610 A 2/1984 Tatros
4,463,654 A 8/1984 Barnes et al.
4,516,466 A 5/1985 Jennie
4,580,484 A 4/1986 Moore
4,656,993 A 4/1987 Yuzawa et al.
4,658,702 A 4/1987 Tatros
4,693,170 A 9/1987 Atchisson
4,697,495 A 10/1987 Beretta
4,787,288 A 11/1988 Miller
4,937,964 A 7/1990 Crandall
5,149,898 A 9/1992 Chesnut et al.
5,183,959 A 2/1993 McCoan et al.
5,223,649 A 6/1993 Claridge
5,339,721 A 8/1994 Beretta
5,517,897 A 5/1996 Perrine
5,614,691 A 3/1997 Taylor
5,623,114 A 4/1997 Soper
5,682,699 A 11/1997 Gentry
5,701,698 A 12/1997 Wesp et al.
5,704,153 A 1/1998 Kaminski et al.
5,760,328 A 6/1998 Robbins
5,770,814 A 6/1998 Ealovega
6,101,918 A 8/2000 Akins
6,360,467 B1 3/2002 Knight
6,601,331 B2 8/2003 Salvitti
6,718,680 B2 4/2004 Roca et al.

6,722,072 B1 4/2004 McCormick
6,851,346 B1 2/2005 Herring
6,889,459 B1 5/2005 Salvitti
6,976,416 B2 12/2005 Ealovega
7,051,638 B2 5/2006 Thomele
7,162,824 B1 1/2007 McCormick
7,213,359 B2 5/2007 Beretta
7,293,385 B2 11/2007 McCormick
7,337,574 B2 3/2008 Crandall et al.
7,347,021 B1 3/2008 Jones
7,398,723 B1 7/2008 Blakley
7,421,937 B1 9/2008 Gangl
7,634,959 B2 12/2009 Frickey
7,661,220 B2 2/2010 Crandall et al.
7,806,039 B1 10/2010 Gomez
8,037,805 B1 10/2011 Neroni
8,112,928 B2 2/2012 Keough
8,127,658 B1 3/2012 Cottle
8,156,854 B2 4/2012 Brown
8,443,537 B2 5/2013 Curry
8,464,454 B2 6/2013 Martin et al.
8,490,309 B2 7/2013 Zukowski
8,667,881 B1 3/2014 Hawbaker
8,695,477 B2 4/2014 Esch
8,720,096 B2 5/2014 Siddle
8,820,211 B1 9/2014 Hawbaker
8,893,607 B2 11/2014 Audibert et al.
8,925,234 B1 1/2015 Barrett
8,985,006 B1 3/2015 Christensen et al.
9,016,187 B2 4/2015 Findlay
9,021,732 B2 5/2015 Johnson
9,021,733 B1 5/2015 DiChario
9,052,150 B2 6/2015 Talasco
9,121,661 B2 9/2015 Calvete
9,146,066 B1 9/2015 Cason
9,146,067 B2 9/2015 Stakes
9,182,189 B2 11/2015 Seigler
9,228,786 B2 1/2016 Sullivan et al.
9,310,150 B1 4/2016 Geissele
9,347,726 B1 5/2016 Thomas
9,448,023 B2 9/2016 Sheets, Jr. et al.
9,476,660 B2 10/2016 Potter et al.
9,513,076 B2 12/2016 Kolev et al.
9,568,264 B2 2/2017 Graves
9,618,288 B2 4/2017 Wilson
9,618,289 B1 4/2017 Geissele
9,625,231 B1 4/2017 Hass
9,631,886 B2 4/2017 Findlay
9,651,329 B2 5/2017 Hittmann
9,658,007 B2 5/2017 Withey
9,683,800 B2 6/2017 Sewell, Jr. et al.
9,733,031 B1 8/2017 Sylvester et al.
9,759,504 B2 9/2017 Geissele
9,777,980 B2 10/2017 Heizer
9,810,493 B2 11/2017 Fluhr et al.
9,810,496 B2 11/2017 Kolev et al.
9,816,772 B2 11/2017 Graves
9,829,263 B2 11/2017 Bonner
9,835,398 B2 12/2017 Biegel
9,863,730 B2 1/2018 Elftmann
9,869,522 B2 1/2018 Larson, Jr. et al.
9,874,417 B2 1/2018 Zajk et al.
9,927,197 B1 3/2018 Geissele
9,939,221 B2 4/2018 Graves
10,002,500 B2 6/2018 Hall et al.
10,006,734 B1 6/2018 Findlay
10,030,924 B1 7/2018 Smith
10,077,960 B2 9/2018 Geissele
10,107,580 B2 10/2018 Fellows et al.
10,254,067 B2 4/2019 Foster
10,267,584 B2 4/2019 Kasanjian-King
10,330,413 B2 6/2019 Williams et al.
10,488,136 B2 11/2019 Sullivan et al.
10,502,511 B2 12/2019 Graves
10,514,223 B1 12/2019 Rounds
10,584,932 B2 3/2020 Foster
10,816,297 B1 10/2020 Williams et al.
11,287,205 B2 3/2022 Biegel
11,293,715 B1 4/2022 Newsome et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

11,346,627	B1	5/2022	DeMonico	
11,724,003	B2 *	8/2023	Strbac	A61L 24/0031 42/69.01
12,036,336	B2 *	7/2024	Strbac	A61L 24/0031
12,274,807	B2 *	4/2025	Strbac	A61L 24/0036
2006/0048426	A1	3/2006	Crandall	
2006/0101695	A1	5/2006	Longueira	
2007/0051236	A1	3/2007	Groves et al.	
2007/0199435	A1	8/2007	Hochstrate et al.	
2009/0151213	A1	6/2009	Bell	
2009/0188145	A1	7/2009	Fluhr et al.	
2011/0209607	A1	9/2011	St. George	
2013/0118343	A1	5/2013	Hirt	
2014/0311004	A1	10/2014	Barrett	
2016/0010933	A1	1/2016	Bonner	
2016/0102933	A1	4/2016	Graves	
2016/0161202	A1	6/2016	Larue	
2017/0176124	A1	6/2017	Wilson	
2017/0219307	A1	8/2017	Foster	
2017/0276447	A1	9/2017	Foster	
2017/0284761	A1	10/2017	Lewis et al.	
2017/0299309	A1	10/2017	Fellows et al.	
2017/0328663	A1	11/2017	Fellows et al.	
2018/0066911	A1	3/2018	Graves	
2018/0087860	A1	3/2018	Sullivan et al.	
2018/0112944	A1	4/2018	Underwood et al.	
2018/0195823	A1	7/2018	Schafer et al.	
2018/0202740	A1	7/2018	Elftmann, Jr.	
2018/0231342	A1	8/2018	Martinez	
2020/0191513	A1	6/2020	Foster	
2021/0222974	A1	7/2021	Graves	
2022/0364812	A1	11/2022	Fellows	
2023/0097725	A1	3/2023	Davis et al.	

FOREIGN PATENT DOCUMENTS

EP	1678458	B1	2/2012
EP	2950033	B1	11/2016
TW	409847	U	10/2000
WO	2016/028337	A1	2/2016
WO	2018/058174	A1	4/2018

OTHER PUBLICATIONS

<https://gundigest.com/gun-reviews/gun-accessories/tac-con-3mr-trigger-shelton>, “Tac-Con 3MR Triggers Aiming at Speed, Accuracy,” Gun Digest (Jan. 2, 2014).

<https://www.americanrifleman.org/content/tac-con-3mr-trigger-system/> “Tac-Con 3MR Trigger System,” American Rifleman (Jan. 14, 2014).

<https://archive.smallarmsreview.com/display.article.cfm?idarticles=2429> Todd Burgreen, “Tactical Fire Control Tac-Con 3MR Trigger: Hype or True Enhancement?,” Small Arms Review (Feb. 21, 2014) (Article ID 2429).

<https://archive.smallarmsreview.com/display.article.cfm?idarticles=2646> Chris A. Choat, “Tac-Con 3MR Trigger,” Small Arms Review (May 16, 2014) (Article ID 2646).

<https://www.shootingillustrated.com/content/tac-con-introduces-ar-15-and-ak-platform-triggers/> Shooting Illustrated, “Tac-Con Introduces AR-15 and AK-Platform Triggers,” (posted on or about Nov. 25, 2014).

<https://www.shootingsportsretailer.com/gear/video-review-tac-con-3mr-trigger-1> Shooting Sports Retailer materials dated Sep. 4, 2014.

<https://www.shootingillustrated.com/content/taccon-3mr-trigger/> Grazio, “TacCon 3MR Trigger,” Shooting Illustrated, May 15, 2015.

<https://www.recoilweb.com/franklin-armory-releases-binary-firing-system-73759.html> Recoil, , “Franklin Armory Releases ‘Binary Firing System’,” Sep. 2015.

<https://gunsamerica.com/digest/fostechs-echo-trigger-fires-rapid-fire-double-taps/> GunsAmerica Digest, “Fostech’s ‘Echo’ Trigger Fires Rapid-Fire Double-Taps,” Jan. 21, 2016.

<https://www.ar15.com/forums/ar-15/How-the-Fostech-Echo-controls-timing---short-video-/118-709932/> “How the Fostech Echo controls timing—short video..” Feb. 20, 2017.

<https://www.globenewswire.com/news-release/2021/09/22/2301309/0/en/Introducing-the-Wide-Open-Trigger.html> GlobeNewswire press release. Big Daddy Unlimited’s “Wide Open Trigger,” Sep. 22, 2021.

<https://www.theoutdoorwire.com/releases/5b6cfb8c-0039-4100-ad16-7a801478e14d/> The Outdoor Wire, “Big Daddy Unlimited’s Wide Open Trigger,” Sep. 21, 2021.

<https://www.youtube.com/watch?v=5MfLYgTe6NI> “How a Brown-ing Auto-5 works | World of Guns,” Jul. 27, 2017.

* cited by examiner




FIG. 1





FIG. 2






FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D

FIREARM TRIGGER MECHANISM**RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 18/665,926 filed May 16, 2024, which is a continuation of U.S. patent application Ser. No. 18/346,423 filed Jul. 3, 2023, now U.S. Pat. No. 12,036,336 issued Jul. 16, 2024, which is a continuation of U.S. patent application Ser. No. 18/048,572 filed Oct. 21, 2022, now U.S. Pat. No. 11,724,003 issued Aug. 15, 2023, which claims the priority benefit of U.S. Provisional Patent Application No. 63/297,884 filed Jan. 10, 2022, all of which are hereby incorporated by reference herein as if fully set forth in their entirety.

TECHNICAL FIELD

The present invention relates generally to a firearm trigger mechanism, and more particularly to a semiautomatic trigger that is selectively mechanically reset by movement of the bolt carrier.

BACKGROUND

In a standard semiautomatic firearm, actuation of the trigger releases a sear, allowing a hammer or striker to fire a chambered ammunition cartridge. Part of the ammunition's propellant force is used to cycle the action, extracting and ejecting a spent cartridge and replacing it with a loaded cartridge. The cycle includes longitudinal reciprocation of a bolt and/or carrier, which also resets the hammer or striker.

A standard semiautomatic trigger mechanism includes a disconnecter, which holds the hammer or striker in a cocked position until the trigger member is reset to engage the sear. This allows the firearm to be fired only a single time when the trigger is pulled and held, because the user is not typically able to release the trigger rapidly enough so that the sear engages before the bolt or bolt carrier returns to its in-battery position. The disconnecter prevents the firearm from either firing multiple rounds on a single pull of the trigger, or from allowing the hammer or striker to simply "follow" the bolt as it returns to battery without firing a second round, but leaving the hammer or striker uncocked.

For various reasons, shooters desire to increase the rate of semiautomatic fire. Sometimes this is simply for entertainment and the feeling of shooting a machine gun. In the past, users have been known to employ "bump firing" to achieve rapid semiautomatic fire. Bump firing uses the recoil of the semiautomatic firearm to fire shots in rapid succession. The process involves bracing the rifle with the non-trigger hand, loosening the grip of the trigger hand (but leaving the trigger finger in its normal position in front of the trigger), and pushing the rifle forward in order to apply pressure on the trigger from the finger while keeping the trigger finger stationary. When fired with the trigger finger held stationary, the firearm will recoil to the rear and allow the trigger to reset as it normally does. When the non-trigger hand pulls the firearm away from the body and back forward toward the original position, it causes the trigger to be pressed against the stationary finger again, firing another round as the trigger is pushed back.

Devices for increasing the rate of semiautomatic fire are shown in U.S. Pat. Nos. 9,568,264; 9,816,772; and 9,939,221, issued to Thomas Allen Graves. The devices shown in these patents forcefully reset the trigger with rigid mechanical contact between the trigger member and the bolt as the action cycles. To adapt this invention to an AR-pattern

firearm, for example, would require not only a modified fire control mechanism, but also a modified bolt carrier.

Other devices for increasing the rate of semiautomatic fire are shown in U.S. Pat. Nos. 10,514,223 and 11,346,627, which are hereby incorporated by reference herein as if fully set forth in their entirety. In these devices the hammer forces the trigger to the set position, and a locking bar prevents early hammer release.

Another device for increasing the rate of semiautomatic fire is shown in U.S. Pat. No. 7,398,723, issued to Brian A. Blakley, and is hereby incorporated by reference herein as if fully set forth in its entirety. The device shown in this patent has a pivoting cam which is contacted by the rearwardly traveling bolt carrier, pivoting the cam rearwardly such that the bottom surface of the cam presses downward on the trigger-extension, forcing the rear of the trigger down, and thereby moving forward the surface of the trigger that an operator's finger engages. Another device for increasing the rate of semiautomatic fire employing a pivoting cam arrangement is shown in U.S. Provisional Patent Application No. 63/374,941 filed Sep. 8, 2022, also invented by Brian A. Blakley, and which is hereby incorporated by reference herein as if fully set forth in its entirety. This pivoting cam arrangement incorporates a three-position safety selector and associated structure to provide safe, standard semiautomatic, and forced reset semi-automatic modes.

Further improvement in forced reset triggers is desired.

SUMMARY OF INVENTION

The present invention provides a semiautomatic trigger mechanism for increasing rate of fire that can be retrofitted into popular existing firearm platforms. In particular, this invention provides a trigger mechanism that can be used in AR-pattern firearms with an otherwise standard M16-pattern bolt carrier assembly. The present invention is particularly adaptable for construction as a "drop-in" replacement trigger module that only requires insertion of two assembly pins and the safety selector. Advantageously, the present invention provides a "three position" trigger mechanism having safe, standard semi-automatic, and forced reset semi-automatic positions.

In one aspect, a firearm trigger mechanism comprises a hammer having a sear catch and a hook for engaging a disconnecter and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse hammer pivot axis between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of a bolt carrier, a trigger member having a sear and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions, the trigger member having a surface positioned to be contacted by the hammer during rearward pivoting of the hammer to cause the trigger member to be forced to the set position, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and adapted to be mounted in the fire control mechanism pocket to pivot on the transverse trigger member pivot axis, a locking member adapted to be mounted in the fire control mechanism pocket to pivot on a transverse locking member pivot axis, the locking member being pivotable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position and a second position at which the locking member

3

does not mechanically block the trigger member allowing the trigger member to be moved to the released position, the locking member spring biased toward the first position and adapted to be moved against the spring bias to the second position by contact from the bolt carrier during forward movement of the bolt carrier as the bolt carrier reaches a substantially in-battery position, and a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer such that the disconnecter hook catches the hammer hook, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer causing the trigger member to be forced to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter when the bolt carrier reaches the substantially in-battery position the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

The safety selector can have a protuberance thereon which, when the safety selector is in the forced reset semi-automatic position, contacts the disconnecter preventing the disconnecter hook from catching the hammer hook. The trigger mechanism can further include a spring which biases the trigger member towards the set position.

In another aspect, a firearm trigger mechanism comprises a housing having a first pair of transversely aligned openings for receiving a hammer pin and a second pair of transversely aligned openings for receiving a trigger member pin, a hammer having a sear catch and a hook for engaging a disconnecter and mounted in the housing to pivot on the hammer pin between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of a bolt carrier, a trigger member having a sear and mounted in the housing to pivot on the trigger member pin between set and released positions, the trigger member having a surface positioned to be contacted by the hammer during rearward pivoting of the hammer to cause the trigger member to be forced to the set position, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and mounted in the housing to pivot on the trigger member pin, a locking member mounted in the housing to pivot on a transverse locking member pin, the locking member being pivotable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position and a second position at which the locking member does not mechanically block the trigger member allowing the trigger member to be moved to the released position, the locking member spring biased toward the first position and adapted to be moved against the spring bias to the second position by contact from the bolt carrier during forward movement of the bolt carrier as the bolt carrier reaches a substantially in-battery position, and a safety selector adapted to be mounted in a fire control mechanism pocket of a receiver to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer such that the

4

disconnecter hook catches the hammer hook, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer causing the trigger member to be forced to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter when the bolt carrier reaches the substantially in-battery position the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

The safety selector can have a protuberance thereon which, when the safety selector is in the forced reset semi-automatic position, contacts the disconnecter preventing the disconnecter hook from catching the hammer hook. The transversely aligned pairs of openings in the housing for receiving the hammer and trigger member pins can be adapted to be aligned with assembly pin openings in the fire control mechanism pocket. The trigger mechanism can further include a spring which biases the trigger member towards the set position. The spring can be a compression spring positioned between a forward end of the trigger member and a floor of the housing.

In another aspect, a firearm comprises a receiver having a fire control mechanism pocket therein, a reciprocating bolt carrier, a hammer having a sear catch and a hook for engaging a disconnecter and mounted in the fire control mechanism pocket to pivot on a transverse hammer pivot axis between set and released positions, the hammer pivoted rearward by rearward movement of the bolt carrier, a trigger member having a sear and mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions, the trigger member having a surface positioned to be contacted by the hammer during rearward pivoting of the hammer to cause the trigger member to be forced to the set position, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and mounted in the fire control mechanism pocket to pivot on the transverse trigger member pivot axis, a locking member mounted in the fire control mechanism pocket to pivot on a transverse locking member pivot axis, the locking member being pivotable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position and a second position at which the locking member does not mechanically block the trigger member allowing the trigger member to be moved to the released position, the locking member spring biased toward the first position and moved against the spring bias to the second position by contact from the bolt carrier during forward movement of the bolt carrier as the bolt carrier reaches a substantially in-battery position, and a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer such that the disconnecter hook catches the hammer hook, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rear-

5

ward movement of the bolt carrier causes rearward pivoting of the hammer causing the trigger member to be forced to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter when the bolt carrier reaches the substantially in-battery

position the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

The firearm can further comprise a housing having a first pair of transversely aligned openings with a hammer pin therethrough and a second pair of transversely aligned openings with a trigger member pin therethrough, the hammer mounted on the hammer pin, the trigger member and disconnecter mounted on the trigger member pin. The firearm can further comprise the receiver having a first pair of transversely aligned assembly pin openings and a second pair of transversely aligned assembly pin openings, the housing first pair of openings coaxial with the receiver first pair of openings and the housing second pair of openings coaxial with the receiver second pair of openings, a first assembly pin passing through the receiver first pair of openings and through the housing first pair of openings, and a second assembly pin passing through the receiver second pair of openings and through the housing second pair of openings. The firearm can further include a spring which biases the trigger member towards the set position. The spring can be a compression spring positioned between a forward end of the trigger member and a floor of the housing.

In another aspect, a firearm trigger mechanism comprises a hammer having a sear catch and a hook for engaging a disconnecter and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse hammer pivot axis between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of a bolt carrier, a trigger member having a sear and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse trigger member pivot axis between set and released positions, the trigger member having a surface positioned to be contacted by a surface of the hammer during rearward pivoting of the hammer to cause the trigger member to be forced to the set position, wherein the sear and sear catch are in engagement in the set positions of the hammer and trigger member and are out of engagement in the released positions of the hammer and trigger member, a disconnecter having a hook for engaging the hammer and adapted to be mounted in the fire control mechanism pocket to pivot on the transverse trigger member pivot axis, a locking member adapted to be movably mounted in the fire control mechanism pocket, the locking member being movable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position and a second position at which the locking member does not mechanically block the trigger member allowing the trigger member to be moved to the released position, the locking member spring biased toward the first position and adapted to be moved against the spring bias to the second position by contact from the bolt carrier during forward movement of the bolt carrier as the bolt carrier reaches a substantially in-battery position, and a safety selector adapted to be mounted in the fire control mechanism pocket to pivot between safe, standard semi-automatic, and forced reset semi-automatic positions. In the standard semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer such that the disconnecter hook catches the hammer hook, at which time a user must manually release the trigger member to free the hammer from the disconnecter to permit

6

the hammer and trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm. In the forced reset semi-automatic position, rearward movement of the bolt carrier causes rearward pivoting of the hammer causing the trigger member to be forced to the set position, the safety selector preventing the disconnecter hook from catching the hammer hook, and thereafter when the bolt carrier reaches the substantially in-battery position the user can pull the trigger member to fire the firearm without manually releasing the trigger member.

Other aspects, features, benefits, and advantages of the present invention will become apparent to a person of skill in the art from the detailed description of various embodiments with reference to the accompanying drawing figures, all of which comprise part of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

Like reference numerals are used to indicate like parts throughout the various drawing figures, wherein:

FIG. 1 is a top front right perspective view of a drop-in trigger module for an AR-pattern firearm according to one embodiment of the invention.

FIG. 2 is a top rear right perspective view thereof.

FIG. 3 is a top rear right exploded perspective view thereof.

FIG. 4A is a top rear right cross-sectional view thereof with the safety selector in the safe position and with the hammer and trigger member in their set positions.

FIG. 4B is a bottom rear right cross-sectional view thereof with the safety selector in the safe position and with the hammer and trigger member in their set positions.

FIG. 5A is a top rear right cross-sectional view thereof with the safety selector in the standard semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 5B is a bottom rear right cross-sectional view thereof with the safety selector in the standard semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 6A is a top rear right cross-sectional view thereof with the safety selector in the forced reset semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 6B is a bottom rear right cross-sectional view thereof with the safety selector in the forced reset semi-automatic position and with the hammer and trigger member in their set positions.

FIG. 7 is a cross-sectional view showing the trigger module installed in a typical AR15-pattern lower receiver, with the hammer and trigger member in their set positions and with the bolt carrier in an in-battery position, and with the safety selector in the safe position.

FIG. 8A is a view similar to FIG. 7 but with the safety selector in the standard semi-automatic position.

FIG. 8B is a view similar to FIG. 8A but after the trigger has been pulled to drop the hammer.

FIG. 8C is a view similar to FIG. 8B but with the bolt carrier cycling to the rear to pivot the hammer.

FIG. 8D is a view similar to FIG. 8C but with the bolt carrier having returned to battery and the disconnecter having caught the hammer.

FIG. 9A is a view similar to FIG. 7 but with the safety selector in the forced reset semi-automatic position.

FIG. 9B is a view similar to FIG. 9A but after the trigger has been pulled to drop the hammer.

7

FIG. 9C is a view similar to FIG. 9B but with the bolt carrier cycling to the rear to pivot the hammer.

FIG. 9D is a view similar to FIG. 9C but with the bolt carrier having returned to battery and the hammer and trigger having returned to their set positions.

DETAILED DESCRIPTION

With reference to the drawing figures, this section describes particular embodiments and their detailed construction and operation. Throughout the specification, reference to “one embodiment,” “an embodiment,” or “some embodiments” means that a particular described feature, structure, or characteristic may be included in at least one embodiment. Thus, appearances of the phrases “in one embodiment,” “in an embodiment,” or “in some embodiments” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the described features, structures, and characteristics may be combined in any suitable manner in one or more embodiments. In view of the disclosure herein, those skilled in the art will recognize that the various embodiments can be practiced without one or more of the specific details or with other methods, components, materials, or the like. In some instances, well-known structures, materials, or operations are not shown or not described in detail to avoid obscuring aspects of the embodiments. “Forward” will indicate the direction of the muzzle and the direction in which projectiles are fired, while “rearward” will indicate the opposite direction. “Lateral” or “transverse” indicates a side-to-side direction generally perpendicular to the axis of the barrel. Although firearms may be used in any orientation, “left” and “right” will generally indicate the sides according to the user’s orientation, “top” or “up” will be the upward direction when the firearm is gripped in the ordinary manner.

Referring first to FIGS. 1-6B, there is illustrated a “drop-in” trigger module 10 adapted for use in an AR-pattern firearm according to a first embodiment of the present invention. As used herein, “AR-pattern” firearm includes the semiautomatic versions of the AR10 and AR15 firearms and variants thereof of any caliber, including pistol caliber carbines or pistols using a blow-back bolt. While select fire (fully automatic capable) versions of this platform, such as the M16 and M4, are also AR-pattern firearms, this invention only relates to semiautomatic firearm actions. The concepts of this invention may be adaptable to other popular semiautomatic firearm platforms, such as the Ruger 10/22™, AK-pattern firearms, and HK-pattern firearms.

The module 10 includes a frame or housing 12 sized and shaped to fit within the internal fire control pocket of an AR-pattern lower receiver 14. Lower receiver parts not important to the present invention are well-known in the art and are omitted from the figures for clarity. The housing 12 includes forward left and right sidewalls 16, 18 which extend substantially vertically and parallel to one another in a laterally spaced-apart relationship. The sidewalls 16, 18 may be interconnected by a floor 20. Shorter, more narrowly spaced apart and substantially vertical and parallel rear sidewalls 21, 22 extend rearward from forward sidewalls 16, 18 and are interconnected by a rear end wall 23. The sidewalls 16, 18 include first and second pairs of aligned openings 24, 26 for receiving hollow transverse pins 30, 32 upon which a hammer 36 and trigger member 38 pivot. The openings 24, 26 are located coaxially with openings 42, 44 in the lower receiver 14. Standard AR-pattern hammer and trigger pins 46, 48 pass through the openings 42, 44 in the lower receiver 14 and through the hollow transverse pins 30,

8

32 to assemble the housing 12 into the lower receiver 14. Thus, the pins 30, 32 retain the hammer 36 and trigger member 38 in the housing 12 in modular fashion, whereas the pins 46, 48 retain the trigger module 10 in the lower receiver 14.

The hammer 36 has a hammer head 50, a sear catch 52, a hammer hook 53, and a concave contact surface 51. The hammer 36 is spring biased towards a forward position by a standard AR-pattern hammer torsion spring (not shown).

The trigger member 38 has a trigger blade 54 that extends downwardly. The trigger blade 54 is the part of the trigger member 38 contacted by a user’s finger to actuate the trigger mechanism. The trigger blade 54 may be curved (as shown) or straight, as desired. The trigger member 38 has a sear 56. When the sear 56 and the sear catch 52 are engaged, the hammer 36 and trigger member 38 are in their set positions. When the sear 56 and sear catch 52 are not engaged, the hammer 36 and trigger member 38 are in their released positions. The trigger member 38 has a convex contact surface 58 that interacts with concave surface 51 on hammer 36 in a manner described below. The trigger member 38 also has a contact surface 69. The trigger member 38 is spring biased by a compression spring 59 positioned between a forward end of the trigger member 38 and the floor 20 of the housing 12 so that the trigger blade 54 is spring biased towards a forward position.

A disconnecter 60 is pivoted on the hollow transverse pin 32 upon which the trigger member 38 pivots. The disconnecter 60 has a disconnecter hook 64 and a tail 66. The tail 66 of the disconnecter 60 is spring biased upwardly away from a tail 68 of the trigger member 38 by a compression spring 67.

A locking or blocking member 72 is movably mounted to the housing 12. For example, the locking/blocking member 72 can be pivoted on a locking/blocking member pin or screw 74 that is installed in aligned openings 76 in the sidewalls 21, 22 of the housing 12. The locking member 72 has a first contact surface 78 that interacts with an engagement surface 94 in a rear portion 96 of a bolt carrier body 98 of a bolt carrier assembly 92, in a manner to be described below. The locking member 72 has a second contact surface 80 that interacts with surface 69 of trigger member 38 in a manner to be described below. The locking member 72 is spring biased by a torsion spring 82 acting between a pin 84 in the sidewalls 21, 22 and a lower portion of the locking member 72 such that surface 78 is biased rearward and surface 80 is biased forward. Alternatively, the locking/blocking member 72 can be slidably mounted to the housing 12 and spring biased forward by a compression spring.

An upper receiver 90 houses a bolt carrier assembly 92. As is well-known in the art, the bolt carrier assembly 92 (or blow-back bolt) slidably reciprocates in the upper receiver 90 and engages the breach of a barrel or barrel extension. As used herein, “bolt carrier” and “bolt carrier assembly” may be used interchangeably and include a blow-back type bolt used in pistol caliber carbine configurations of the AR-platform. The bolt carrier assembly 92 used with the embodiments of this invention can have either a standard mil-spec M16-pattern bolt carrier, a standard AR15-pattern bolt carrier, or some variation of the two, depending on the design of the locking member 72, and whether operated by a gas direct impingement system or a gas piston system. The bolt carrier assembly 92 has an engagement surface 94 in a rear portion 96 of the bolt carrier body 98. As in an ordinary AR15-pattern configuration, during rearward travel of the bolt carrier assembly 92 a lower surface 102 in a forward portion 104 of the bolt carrier body 98 contacts the face of

the hammer head 50 causing the hammer 36 to pivot rearward. Rearward travel of bolt carrier assembly 92 also moves engagement surface 94 rearward and away from surface 78 of locking member 72. The action of spring 82 causes locking member 72 to pivot in a first direction from a first position wherein surface 80 of locking member 72 does not impede upward movement of surface 69 of trigger member 38 to a second position wherein surface 80 of locking member 72 does impede upward movement of surface 69 of trigger member 38 thus preventing the trigger blade 54 from being pulled by the user. During forward travel of the bolt carrier assembly 92 the engagement surface 94 of the bolt carrier body 98 contacts the surface 78 of the locking member 72 to pivot the locking member 72 in a second opposite direction from the second position to the first position.

A three position safety selector 110 has safe, standard semi-automatic, and forced reset semi-automatic positions. When in the safe position (safety selector indicator 111 pointing forward), a wide semi-circular portion 112 of the safety selector 110 prevents the trigger blade 54 from being pulled (FIGS. 4A, 4B, and 7). When in the standard semi-automatic position (safety selector indicator 111 pointing upward), a flat portion 114 of the safety selector 110 permits the trigger blade 54 to be pulled. The disconnecter 60 can pivot with the trigger member 38 and the disconnecter hook 64 can catch the hammer hook 53 during rearward pivoting travel of the hammer head 50. (FIGS. 5A and 5B). When in the forced reset semi-automatic position (safety selector indicator 111 pointing rearward), a narrow semi-circular portion 116 permits the trigger blade 54 to be pulled but prevents the disconnecter 60 from pivoting with the trigger member 38 thus preventing the disconnecter hook 64 from catching the hammer hook 53 during rearward pivoting travel of the hammer head 50. (FIGS. 6A and 6B). In other words, in the forced reset semi-automatic position, the disconnecter 60 is "disabled" in that the disconnecter hook 64 is unable to catch the hammer hook 53 during cycling of the bolt carrier assembly 92.

Referring now to FIGS. 8A-8D, with the safety selector 110 set in the standard semi-automatic position, rearward finger pressure on the trigger blade 54 causes the trigger member 38 to rotate clockwise. Rotation of the trigger member 38 causes the sear 56 to disengage from the sear catch 52 of the hammer 36. This allows the hammer 36 to drop by spring force onto the firing pin 99 of the bolt carrier assembly 92, discharging an ammunition cartridge (not shown), and causing the action to cycle by moving the bolt carrier assembly 92 rearward. Rearward travel of the bolt carrier assembly 92 frees the locking member 72 to pivot such that surface 80 is moved into a blocking position. Rearward travel of the bolt carrier assembly 92 also causes the lower surface 102 to contact the face of the hammer head 50 and pivot the hammer 36 counter-clockwise. During pivoting travel of the hammer 36 surface 51 contacts surface 58 of trigger member 38 forcing trigger member 38 to pivot counter-clockwise. Also during pivoting travel of the hammer 36 the disconnecter hook 64 catches the hammer hook 53. Forward travel of the bolt carrier assembly 92 returning to battery causes the surface 94 to contact the surface 78 of the locking member 72 to pivot the locking member 72 clockwise moving surface 80 out of the blocking position. At this point rearward finger pressure on the trigger blade 54 must be released to allow the sear 56 to engage the sear catch 52, returning the hammer 36 and trigger member 38 to their set positions. Thereafter the user can reapply rearward finger pressure on the trigger blade 54 to fire another round.

Referring now to FIGS. 9A-9D, with the safety selector 110 set in the forced reset semi-automatic position, rearward finger pressure on the trigger blade 54 causes the trigger member 38 to rotate clockwise. The narrow semi-circular portion 116 of the safety selector 110 prevents the disconnecter 60 from rotating with the trigger member 38, thus "disabling" the disconnecter 60, preventing the disconnecter hook 64 from catching the hammer hook 53. Rotation of the trigger member 38 causes the sear 56 to disengage from the sear catch 52 of the hammer 36. This allows the hammer 36 to drop by spring force onto the firing pin 99 of the bolt carrier assembly 92, discharging an ammunition cartridge, and causing the action to cycle by moving the bolt carrier assembly 92 rearward. Rearward travel of the bolt carrier assembly 92 frees the locking member 72 to pivot such that surface 80 is moved into a blocking position. Rearward travel of the bolt carrier assembly 92 also causes the lower surface 102 to contact the face of the hammer head 50 and pivot the hammer 36 counter-clockwise. During pivoting travel of the hammer 36 surface 51 contacts surface 58 of trigger member 38 forcing trigger member 38 to pivot counter-clockwise. The bolt carrier assembly 92 thereby forces the hammer 36 and trigger member 38 to their set positions wherein the sear 56 engages the sear catch 52. Forward travel of the bolt carrier assembly 92 returning to battery causes the surface 94 to contact the surface 78 of the locking member 72 to pivot the locking member 72 clockwise. At this point the user can reapply rearward finger pressure on the trigger blade 54 to fire another round, without first manually releasing rear finger pressure on the trigger blade 54.

Thus, as the bolt carrier assembly 92 returns forward, the trigger member 38 is held in its set position by the locking member 72. The trigger member 38 cannot be pulled to release the sear/sear catch engagement, thus precluding early hammer release or "hammer follow" against the bolt carrier assembly 92 and firing pin 99 as the bolt carrier assembly 92 is returning to battery. When the bolt carrier assembly 92 has reached (or nearly reached) its closed, in-battery position, the engagement surface 94 contacts and forwardly displaces the contact surface 78 of the locking member 72, disengaging the contact surface 80 of the locking member 72 from the contact surface 69 of the trigger member 38, allowing the trigger blade 54 to be pulled. Again, this prevents early hammer release and contact of the hammer against the firing pin before the bolt is completely locked and in-battery.

While various embodiments of the present invention have been described in detail, it should be apparent that modifications and variations thereto are possible, all of which fall within the true spirit and scope of the invention. Therefore, the foregoing is intended only to be illustrative of the principles of the invention. The invention resides in each individual feature described herein, alone, and in any and all combinations and subcombinations of any and all of those features. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not intended to limit the invention to the exact construction and operation shown and described. Accordingly, all suitable modifications and equivalents may be included and considered to fall within the scope of the invention, defined by the following claim or claims.

What is claimed is:

1. A trigger mechanism for a firearm comprising:

a hammer having a hammer sear surface and a hammer hook and adapted to be mounted in a fire control mechanism pocket of a receiver to pivot on a transverse

11

- hammer pivot axis between set and released positions, the hammer adapted to be pivoted rearward by rearward movement of a bolt means;
- a trigger member having a trigger member sear surface and adapted to be mounted in the fire control mechanism pocket to move between a set position and a released position, rearward pivoting of the hammer causing the trigger member to be forced to the set position;
- wherein the hammer sear surface and trigger member sear surface are in engagement in the set position of the hammer and the set position of the trigger member and are out of engagement in the released position of the hammer and the released position of the trigger member;
- a disconnecter having a disconnecter hook for engaging the hammer hook and adapted to be mounted in the fire control mechanism pocket to pivot on a transverse disconnecter pivot axis
- a locking member adapted to be movably mounted in the fire control mechanism pocket, the locking member being movable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position and a second position at which the locking member does not mechanically block the trigger member allowing the trigger member to be moved to the released position and adapted to be moved to the second position by forward movement of the bolt; and
- a safety selector adapted to be movably mounted in the fire control mechanism pocket to move between at least a safe position, a standard semi-automatic position, and a forced reset-semi-automatic position;
- wherein in the standard semi-automatic position, rearward movement of the bolt means causes rearward pivoting of the hammer such that the disconnecter hook catches the hammer hook, at which time a user must manually release pressure on the trigger member to free the hammer from the disconnecter to permit the hammer and the trigger member to pivot to the set positions so that the user can actuate the trigger member to fire the firearm again; and
- wherein in the forced reset semi-automatic position, rearward movement of the bolt means causes rearward pivoting of the hammer causing the trigger member to be forced to the set position, and the disconnecter hook is prevented from catching the hammer hook, and thereafter when the bolt means reaches a substantially in-battery position or an in-battery position the user can actuate the trigger member to fire the firearm again.
2. The trigger mechanism of claim 1, further comprising a spring which biases the trigger member toward the set position.
3. The trigger mechanism of claim 1, wherein the safety selector is adapted to be pivotably mounted in the fire control mechanism pocket to pivot on a transverse safety selector pivot axis.
4. The trigger mechanism of claim 1, wherein the locking member is adapted to be pivotably mounted in the fire control mechanism pocket to pivot on a transverse locking member pivot axis.
5. The trigger mechanism of claim 1, wherein the trigger member pivots on a transverse trigger member pivot axis between the set position and the released position.
6. The trigger mechanism of claim 1, wherein the locking member is spring biased toward the first position and

12

adapted to be moved against the spring bias to the second position by contact from the bolt means during forward movement of the bolt means.

7. A trigger mechanism operable in a standard semi-automatic mode and in a forced reset semi-automatic mode for a firearm having a semi-automatic cycling action, comprising:

a hammer having a hammer sear surface and a hammer hook and adapted to pivot on a transverse hammer pivot axis between a hammer set position and hammer released position, the hammer adapted to be pivoted rearward by rearward movement of a bolt means;

a trigger member having a trigger member sear surface and adapted to move between a trigger member set position and a trigger member released position, cycling of the action causing the trigger member to be forced to the trigger member set position;

wherein the trigger member sear surface and the hammer sear catch are in engagement in the hammer set position-and the trigger member set position-and are out of engagement in the hammer released position-and the trigger member released position;

a disconnecter having a disconnecter hook for engaging the hammer hook and adapted to pivot on a transverse disconnecter pivot axis; and

a locking member adapted to be movable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position when in at least one mode of operation and a second position at which the locking member does not mechanically block the trigger member allowing said trigger member to be moved to the released position and adapted to be moved to the second position by forward movement of the bolt means,

wherein in the standard semi-automatic mode, rearward movement of the bolt means causes rearward pivoting of the hammer such that the disconnecter hook catches the hammer hook, at which time a user must manually reduce pressure on the trigger member to free the hammer from the disconnecter to permit the hammer and the trigger member to pivot to the hammer set position and the trigger member set position so that the user can actuate the trigger member to fire the firearm again, and

wherein in the forced reset semi-automatic mode, rearward movement of the bolt means causes rearward pivoting of the hammer causing the trigger member to be forced to the trigger member set position, and the disconnecter hook is prevented from holding the hammer hook, and thereafter when the bolt means reaches a substantially in-battery position or an in-battery position the user can actuate the trigger member to fire the firearm again.

8. The trigger mechanism of claim 7, further comprising a spring which biases the trigger member toward the trigger member set position.

9. The trigger mechanism of claim 7, wherein a safety selector is adapted to be pivotably mounted to pivot on a transverse safety selector pivot axis.

10. The trigger mechanism of claim 7, wherein the locking member is adapted to be pivotably mounted in a fire control mechanism pocket to pivot on a transverse locking member pivot axis.

11. The trigger mechanism of claim 7, wherein the trigger member pivots on a transverse trigger member pivot axis between the trigger member set position and the trigger member released position.

13

12. The trigger mechanism of claim 7, wherein the locking member is spring biased toward the first position and adapted to be moved against the spring bias to the second position by contact from the bolt means during forward movement of the bolt means.

13. The trigger mechanism of claim 7, further comprising a safety selector that is a separate part from the locking member.

14. A trigger mechanism for a firearm operable in at least a standard semi-automatic mode and a forced reset semi-automatic mode, comprising:

a hammer having a hammer sear catch and a hammer hook and adapted to pivot on a transverse hammer pivot axis between a set position and a released position, the hammer adapted to be pivoted rearward by rearward movement of a bolt means;

a trigger member having a trigger member sear and adapted to move between a set position and a released position, the trigger member being forced to the set position as a result of cycling action of the bolt means, such that the trigger member sear and the hammer sear catch are in engagement in the set position of the hammer and the set position of the trigger member and are out of engagement in the released position of the hammer and the released position of the trigger member;

wherein the trigger member sear and the hammer sear catch are in engagement in the set position of the hammer and the set position of the trigger member and are out of engagement in the released position of the hammer and the released position of the trigger member,

a disconnecter having a disconnecter hook for engaging the hammer hook and adapted to pivot on a transverse disconnecter pivot axis; and

a locking member adapted to be movably mounted, the locking member being movable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position and a second position at which the locking member does not mechanically block the trigger member allowing the trigger member to be moved to the released position and adapted to be moved to the second position by forward movement of the bolt means,

wherein in the standard semi-automatic mode, rearward movement of the bolt means causes rearward pivoting of the hammer such that the disconnecter hook holds the hammer hook, at which time a user must manually reduce pressure on the trigger member to free the hammer from the disconnecter to permit the hammer and the trigger member to pivot to the set positions so that the user can pull the trigger member to fire the firearm again; and

wherein in the forced reset semi-automatic mode, rearward movement of the bolt means causes the trigger member to be forced to the set position, and the disconnecter hook is prevented from holding the hammer hook, and thereafter when the bolt means reaches a substantially in-battery position or an in-battery position the user can actuate the trigger member to fire the firearm again.

15. The trigger mechanism of claim 14, further comprising a safety selector, movement of which selects between at least standard semi-automatic mode and forced reset semi-automatic mode.

14

16. A trigger mechanism for a firearm comprising:

a hammer having a hammer sear catch and a hammer hook and adapted to pivot on a transverse hammer pivot axis between a hammer set position and a hammer released position, the hammer adapted to be pivoted rearward by rearward movement of a bolt means;

a trigger member having a trigger member sear and adapted to move between a trigger member set position and a trigger member released position, the trigger member being forced to the trigger member set position as a result of cycling action of the bolt means;

wherein the trigger member sear and the hammer sear catch are in engagement in the hammer set position and trigger member set position and are out of engagement in the hammer released position and the trigger member released position;

a disconnecter having a disconnecter hook for engaging the hammer hook and adapted to pivot on a transverse disconnecter pivot axis;

a locking member adapted to be movably mounted, the locking member being movable between a first position at which the locking member mechanically blocks the trigger member from moving to the trigger member released position and a second position at which the locking member does not mechanically block the trigger member allowing the trigger member to be moved to the trigger member released position and adapted to be moved to the second position by forward movement of the bolt means; and

a safety selector adapted to be movably mounted to move between at least standard semi-automatic position and forced reset semi-automatic position, wherein in the standard semi-automatic position, rearward movement of the bolt means causes rearward pivoting of the hammer such that thereafter the disconnecter hook holds the hammer hook, after which a user must reduce rearward pressure on the trigger member before the trigger member can be actuated to fire the firearm again, and

wherein in the forced reset semi-automatic position, rearward movement of the bolt means causes the trigger member to be forced to the set position, the disconnecter hook is prevented from holding the hammer hook, and thereafter, when the bolt means reaches a substantially in-battery position or an in-battery position, the trigger member can be actuated to fire the firearm again.

17. A trigger mechanism for a semi-automatic firearm, comprising:

a hammer comprising a hammer hook;

a disconnecter comprising a disconnecter hook for holding the hammer hook;

a trigger member, wherein the trigger member can be is forced into a trigger set position responsive to rearward motion of a cyclic semi-automatic action of the semi-automatic firearm; and

a locking member configured to move between a block position and a non-block position, wherein the block position mechanically blocks the trigger member from moving from the trigger set position to a trigger released position, wherein the non-block position permits the trigger member to be moved from the trigger set position to the trigger released position, wherein the locking member is moved into the block position during rearward motion of the cyclic semi-automatic

15

action and moved into the non-block position during forward motion of the cyclic semi-automatic action, and wherein:

in a standard semi-automatic mode, after cycling of the action and while the trigger member is in the trigger released position, the trigger mechanism is configured such that the disconnecter hook holds the hammer hook, at which point, rearward pressure on the trigger member must be reduced before the trigger member can be actuated, and

in a forced reset semi-automatic mode, the disconnecter hook is prevented from holding the hammer hook, and the trigger member can be actuated when the cyclic semi-automatic action reaches a substantially in-battery position or an in-battery position.

18. The trigger mechanism of claim 17, wherein the cyclic semi-automatic action comprises a bolt.

19. The trigger mechanism of claim 17, wherein the hammer is configured to pivot on an axis substantially perpendicular to an axis of the cyclic semi-automatic action.

20. The trigger mechanism of claim 17, wherein the hammer is configured to pivot between a hammer set position and a hammer released position.

21. The trigger mechanism of claim 17, wherein the disconnecter is configured to pivot on an axis substantially perpendicular to an axis of the cyclic semi-automatic action.

22. The trigger mechanism of claim 17, wherein the trigger member is configured to pivot on an axis substantially perpendicular to an axis of the cyclic semi-automatic action.

23. The trigger mechanism of claim 17, wherein the trigger member is configured to pivot between the trigger set position and a trigger released position.

24. The trigger mechanism of claim 17, wherein the hammer is configured to pivot rearwardly responsive to rearward motion of the cyclic semi-automatic action.

25. The trigger mechanism of claim 17, wherein the hammer comprises a hammer sear surface and the trigger member comprises a trigger sear surface, and wherein the hammer sear surface and the trigger sear surface are in engagement when, simultaneously, the hammer is in a hammer set position and the trigger member is in the trigger set position.

26. The trigger mechanism of claim 17, wherein the locking member is configured to pivot on an axis substantially transverse to a reciprocation axis of the cyclic semi-automatic action.

27. The trigger mechanism of claim 17, further comprising a spring which biases the trigger member toward the trigger set position.

28. The trigger mechanism of claim 17, comprising a safety selector, wherein the safety selector is configured to be pivotably mounted to pivot on a transverse axis of the semi-automatic firearm and substantially perpendicular to an axis of the cyclic semi-automatic action.

29. The trigger mechanism of claim 17, comprising a safety selector, wherein the safety selector is selectable between at least the standard semi-automatic mode and the forced reset semi-automatic mode.

30. The trigger mechanism of claim 17, comprising a safety selector that is separate from the locking member.

31. The trigger mechanism of claim 17, wherein the locking member is biased by a spring toward the block position.

32. A trigger mechanism for a semi-automatic firearm operable in at least a standard semi-automatic mode and a forced reset semi-automatic mode, comprising:

16

a disconnecter;

a trigger member, wherein the trigger member is forced into a trigger set position responsive to rearward motion of a cyclic semi-automatic action of the semi-automatic firearm; and

a locking member configured to move between a block position and a non-block position, wherein the block position mechanically blocks the trigger member from moving from the trigger set position to a trigger released position, wherein the non-block position permits the trigger member to be moved from the trigger set position to the trigger released position, wherein the locking member is moved into the block position during rearward motion of the cyclic semi-automatic action and moved into the non-block position during forward motion of the cyclic semi-automatic action;

a safety selector, wherein the safety selector is selectable between at least the standard semi-automatic mode and the forced reset semi-automatic mode; and wherein:

in the standard semi-automatic mode, rearward pressure on the trigger member must be reduced to disengage a hammer from the disconnecter before the trigger member can again be actuated; and

in the forced reset semi-automatic mode, the trigger member is forced to the trigger set position and can be actuated without reducing pressure on the trigger member to fire another round when the cyclic semi-automatic action reaches a substantially in-battery position or an in-battery position.

33. The trigger mechanism of claim 1, wherein the bolt means comprises a bolt carrier assembly.

34. The trigger mechanism of claim 7, wherein the bolt means comprises a bolt carrier assembly.

35. The trigger mechanism of claim 14, wherein the bolt means comprises a bolt carrier assembly.

36. The trigger mechanism of claim 16, wherein the bolt means comprises a bolt carrier assembly.

37. A trigger mechanism operable in a standard semi-automatic mode and in a forced reset semi-automatic mode for a firearm having a semi-automatic cycling action, comprising:

a hammer having a hammer sear surface and a hammer hook and adapted to pivot on a transverse hammer pivot axis between a set position and released position, the hammer adapted to be pivoted rearward by a rearward phase of the semi-automatic cycling action;

a trigger member having a trigger member sear surface and adapted to move between a set position and a released position;

wherein the trigger member sear surface and the hammer sear surface are in engagement when the hammer and trigger member are each in their respective set position and are out of engagement when either the hammer or trigger member is not in their respective set position;

a disconnecter having a disconnecter hook and adapted to pivot on a transverse disconnecter pivot axis; and

a locking member adapted to be movable between a first position at which the locking member mechanically blocks the trigger member from moving to the released position when in at least one mode of operation and a second position at which the locking member does not mechanically block the trigger member allowing said trigger member to be moved to the released position and adapted to be moved to the second position by a forward phase of the semi-automatic cycling action; wherein in the standard semi-automatic mode, the rearward phase of the semi-automatic cycling action causes

17

a rearward pivot of the hammer to a position where the hammer hook is past the disconnecter hook, the hammer sear surface is not in engagement with the trigger member sear surface, and, thereafter, rearward pressure on the trigger member must be reduced to permit the hammer and the trigger member to pivot to their respective set positions where the hammer sear surface engages with the trigger member sear surface, so the trigger member can be actuated to fire the firearm again; and

wherein in the forced reset semi-automatic mode the disconnecter hook is prevented from catching the hammer hook and the rearward phase of the semi-automatic cycling action causes (1) rearward pivoting of the hammer to a position where the hammer hook is past the disconnecter hook, (2) the trigger member to be forced to its respective set position, and (3) the hammer sear surface to be not in engagement with the trigger member sear surface, and thereafter, the hammer forwardly pivots to its respective set position with the hammer hook passing the disconnecter hook, the hammer sear surface engages with the trigger member sear surface, and when the forward phase of the semi-automatic cycling action reaches an in-battery position, rearward pressure on the trigger member the trigger member does not need to be released to actuate the trigger member to fire the firearm again.

38. A forced reset trigger mechanism, comprising:
 a hammer having a hammer hook and adapted to pivot on a transverse hammer pivot axis;
 a disconnecter having a disconnecter hook and adapted to pivot on a transverse disconnecter pivot axis;
 a trigger member; and
 a safety selector adapted to be movable between a standard semi-automatic position and a forced reset semi-automatic position,
 wherein when the safety selector is in the standard semi-automatic position and the trigger member is rearwardly actuated, and after the hammer pivots rearward to a position where the hammer hook is past the disconnecter hook, rearward pressure on the trigger member must be reduced to permit the trigger member to then be actuated to fire a firearm.

39. A forced reset trigger mechanism, comprising:
 a hammer having a hammer hook and adapted to pivot on a transverse hammer pivot axis;
 a disconnecter having a disconnecter hook and adapted to pivot on a transverse disconnecter pivot axis;
 a trigger member; and
 a safety selector adapted to be movable between a standard semi-automatic position and a forced reset semi-automatic position,
 wherein, when in either position, when the trigger member is pulled rearward, cycling of a firearm action rearwardly pivots the hammer to a position where the hammer hook is past the disconnecter hook,
 wherein if the safety selector is in the standard semi-automatic position, rearward pressure on the trigger member must be reduced to permit the trigger member to then be actuated to fire a firearm, and
 wherein, if the safety selector is in the forced reset semi-automatic position, the trigger member is forced to move to a full reset position against rearward pressure on the trigger member and the rearward pressure on the trigger member does not need to be reduced to actuate the trigger to fire the firearm.

18

40. A forced reset trigger mechanism, comprising:
 a hammer having a hammer hook and adapted to pivot on a transverse hammer pivot axis;
 a disconnecter having a disconnecter hook and adapted to pivot on a transverse disconnecter pivot axis;
 a trigger member; and
 a safety selector adapted to be movable between a standard semi-automatic position and a forced reset semi-automatic position, wherein, when in either position, when the trigger member is pulled rearward, cycling of a firearm action rearwardly pivots the hammer to a position where the hammer hook is past the disconnecter hook,
 wherein, if the safety selector is in the standard semi-automatic position, rearward pressure on the trigger member must be reduced to permit the trigger member to then be actuated to fire a firearm, and
 wherein, when the safety selector is in the forced reset semi-automatic position, the hammer contacts the trigger member and forces the trigger member to move to a full reset position against rearward pressure on the trigger member and the rearward pressure on the trigger member does not need to be reduced to actuate the trigger to fire the firearm.

41. A forced reset trigger mechanism, comprising:
 a trigger member configured to pivot about a transverse pivot axis and having a thickness defined between opposing lateral side surfaces; and
 a disconnecter positioned laterally adjacent to the trigger member.

42. The trigger mechanism of claim 41, wherein a combined lateral width of the trigger member and the disconnecter is sized to fit within a fire control mechanism pocket.

43. The trigger mechanism of claim 41, wherein the trigger member includes a relieved portion extending inward from one of the opposing lateral side surfaces, the relieved portion being configured to receive at least a portion of the disconnecter.

44. A forced reset trigger mechanism, comprising:
 a trigger member configured to pivot about a transverse pivot axis and having opposing lateral side surfaces; and
 a disconnecter disposed laterally adjacent to the trigger member,
 wherein the trigger member includes a reduced-thickness region defined at one of the opposing lateral side surfaces, and the disconnecter is received at least partially within the reduced-thickness region such that the trigger member and the disconnecter collectively define an overall lateral width.

45. A forced reset trigger mechanism, comprising:
 a trigger member configured to pivot about a transverse pivot axis; and
 a disconnecter positioned laterally adjacent to the trigger member,
 wherein the trigger member defines a lateral accommodation space, and the disconnecter occupies at least a portion of the lateral accommodation space such that the trigger member and the disconnecter overlap laterally.

46. A forced reset trigger mechanism, comprising:
 a trigger member configured to pivot on a transverse trigger pivot axis, a forward of the trigger member comprising a downward oriented stop surface configured to abut an arresting surface that stops travel of the trigger when the trigger is pulled.

19

47. The forced reset trigger mechanism of claim 46, wherein the arresting surface is an interior surface of a trigger cassette housing.

48. A forced reset trigger mechanism, comprising:

a hammer having a hammer hook;

a disconnecter having a disconnecter hook;

a trigger member; and

a safety selector adapted to be movable between a standard semi-automatic position and a forced reset semi-automatic position, wherein when the safety selector is moved from the standard semi-automatic position and into the forced reset semi-automatic position, the disconnecter is moved into a position where, after the hammer hook passes the disconnecter hook during firearm cycling, a reduction in rearward pressure on the trigger member is not required to fire a next shot.

49. A forced reset trigger mechanism, comprising:

a hammer having a hammer hook;

a disconnecter having a disconnecter hook;

a trigger member; and

a safety selector adapted to be movable between a standard semi-automatic position and a forced reset semi-automatic position, wherein when the safety selector is moved from the standard semi-automatic position and into the forced reset semi-automatic position, a portion of the safety selector moves the disconnecter into a position so as to prevent the disconnecter hook from catching the hammer hook where, after the hammer hook passes the disconnecter hook during firearm cycling, a reduction in rearward pressure on the trigger member is not required to fire a next shot.

50. A trigger mechanism operable in a standard semi-automatic mode and in a forced reset semi-automatic mode for a firearm having a semi-automatic cycling action, comprising:

a hammer, having a hammer sear surface and a hammer hook, adapted to pivot on a hammer pivot axis between a hammer set position and a hammer released position, the hammer adapted to pivot rearward by a rearward phase of the semi-automatic cycling action;

a trigger member, having a trigger member sear surface, adapted to move between a trigger set position and a trigger released position;

wherein the trigger member sear surface and the hammer sear surface are in engagement when the hammer and trigger member are both in their respective set position and are out of engagement when either the hammer or trigger member is not in its respective set position;

a disconnecter, having a disconnecter hook for engaging the hammer hook, adapted to pivot on a disconnecter pivot axis; and

a locking member adapted to be movable between a first position, where the locking member mechanically blocks the trigger member from moving from the trigger set position to the trigger released position, and a second position, where the locking member does not mechanically block the trigger member;

wherein said locking member is adapted to be moved from said first position to said second position by a forward phase of the semi-automatic cycling action;

whereas, in the standard semi-automatic mode, the trigger mechanism is configured such that rearward pressure on the trigger member causes the trigger member to move from the trigger set position toward the trigger released position, this movement causes the hammer to

20

move from the hammer set position to the hammer release position, thereafter the hammer is positioned to pivot rearward;

whereas, the semi-automatic cycling action rearwardly pivots the hammer to a position where the hammer hook is below the disconnecter hook;

following rearward pivot of the hammer from the hammer release position and while there is rearward pressure on the trigger member, the hammer hook is configured to engage the disconnecter hook, and thereafter the rearward pressure on the trigger member must be reduced to allow the hammer hook to pivot forward above the disconnecter hook and for the trigger member sear surface to engage with the hammer sear surface;

whereas, in the forced reset semi-automatic mode, the trigger mechanism is configured such that the disconnecter hook is rearwardly displaced such that it cannot engage the hammer hook and rearward movement of the hammer causes the trigger member to move from the trigger released position to the trigger set position despite rearward pressure on the trigger member; and whereas thereafter, the hammer returns to the hammer set position such that the hammer sear surface and the trigger member sear surface are engaged.

51. In a forced reset trigger mechanism, an assembly, comprising:

a trigger housing configured to be mounted in a fire control mechanism pocket of a firearm, the housing supporting a locking member, the locking member configured to be movable between a first position and a second position, wherein in the second position the locking member blocks the trigger from being actuate, and

a safety selector capable of at least standard semi-automatic mode and forced reset semi-automatic mode.

52. A forced reset trigger assembly for installation within a fire control pocket of a firearm, comprising:

a trigger housing configured to be receivable within the fire control pocket;

a trigger member pivotally supported by the trigger housing;

a locking member movably supported by the trigger housing and movable relative to the trigger member, the locking member movable between:

(a) a blocking position in which movement of the trigger member is prevented; and

(b) a non-blocking position in which the trigger member is permitted to move; and

a selector having at least two discrete operating positions including:

(i) a standard semi-automatic position; and

(ii) a forced-reset position in which the trigger assembly operates in a forced reset firing mode.

53. A forced reset trigger mechanism, comprising:

a trigger member configured to pivot about a transverse axis;

a hammer;

a disconnecter operatively associated with the trigger member and the hammer; and

a locking member operatively associated with the trigger member,

wherein cycling of the action causes the trigger member to be forced to the set position in at least one operating mode; and

wherein the trigger mechanism is configured such that, when combined with a selector having an alternate selectable position, the trigger mechanism is enabled

21

for a forced reset operating mode corresponding to the alternate selectable position.

54. A forced reset trigger mechanism, comprising:

- a trigger member configured to pivot about a transverse axis;
- a hammer;
- a disconnecter operatively associated with the trigger member and the hammer;
- a locking member operatively associated with the trigger member;

wherein cycling of the action causes the trigger member to be forcibly returned to a set position in at least one operating mode; and

wherein the trigger mechanism includes a selector interface structured to cooperate with a selector having at least two discrete selectable positions including:

- (i) a standard semi-automatic position; and
- (ii) a forced-reset position,

such that rotation of the selector to the forced reset position enables said forced reset operating mode.

22

55. A forced reset trigger mechanism, comprising:

- a trigger member pivotable about a transverse axis;
- a hammer;
- a disconnecter operatively associated with the trigger member and the hammer;
- a locking member operatively associated with the trigger member;

wherein cycling of the firearm action causes the trigger member to be returned to a set position; and

wherein the trigger mechanism includes a selector interface structured to cooperate with a selector rotatable between at least two discrete positions including:

- (i) a semi-automatic position in which the trigger resets without forced forward drive; and
- (ii) a forced-reset position in which cycling of the action positively drives the trigger member forward to the set position.

* * * * *